



PRODUCT SPECIFICATIONS

Detail Photos

(on right from top to bottom)
Pre-assembled Az/El Mount

Cross-Pol Compensating (XPC)
Ku-band feed assembly

The antenna features a unique feed which provides cross-pol discrimination exceeding industry standards



1.2 m RxTx Class I Antenna System TYPE 123 with XPC Feed

The Skyware Global Type 123 Class I 1.2 m Offset Antenna is a rugged commercial grade product suitable for the most demanding applications.

The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which strengthens the antenna and helps to sustain the necessary parabolic shape. The reflector optics feature a long focal length for excellent cross-pol performance.

The Az/El mount is constructed from heavy-gauge steel to provide a rigid support to the reflector. The Az/El mount secures the antenna to any 73-76 mm (2.88"-3.00") mast and prevents slippage in high winds. A specially formulated powder paint process offers excellent protection from weather-related corrosion.

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- One-piece precision offset thermoset-molded reflector.
- Long focal length optics for low cross-pol performance.
- Available with Ku-band co-pol or cross-pol feeds.
- Galvanized 19 mm (.75 in) O.D. feed support legs for lightweight outdoor units (ODU's).
- Plated hardware for maximum corrosion resistance.
- Class I system designed for typical 1 W and 2 W Ku-band Block Up-Converters.*

* 2 kg or 4.5 lb max. weight for RF electronics (BUC and LNB)

SPECIFICATIONS

Type 123 1.2 m RxTx Class I Antenna System

RF Performance

Effective Aperture	1.2 m (48 in)
Operating Frequency	Tx	13.75 - 14.50 GHz
	Rx	10.70 - 12.75 GHz
Polarization	Linear, Orthogonal
Gain (± 2 dBi)	Tx	43.3 dBi @ 14.3 GHz
	Rx	41.8 dBi @ 12.0 GHz
3 dB Beamwidth	Tx	1.2° @ 14.3 GHz
	Rx	1.5° @ 12.0 GHz
Sidelobe Envelope (Tx, Co-Pol dBi)	1.5° < θ < 20°	29 - 25 Log θ
	20° < θ < 26.3°	-3.5
	26.3° < θ < 48°	32 - 25 Log θ
	48° < θ < 180°	-10
Antenna Cross-Polarization	> 30 dB in 1 dB Contour
Antenna Noise Temperature	10° El	45° K
	20° El	31° K
	30° El	24° K
VSWR	Tx	1.3:1
	Rx	1.5:1
Isolation (Port to Port)	Tx	90 dB
	Rx	> 40 dB
Feed Interface	Tx	WR75 Flat Flange
	Rx	WR75 Flat Flange

Mechanical Performance

Reflector Material	Glass Fiber Reinforced Polyester
Antenna Optics	One-Piece Offset Feed Prime Focus
Mount Type	Elevation over Azimuth
Elevation Adjustment Range	7° - 84° Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous $\pm 20^\circ$ Fine Adjustment
Mast Pipe Interface	73 - 76 mm (2.88 in - 3.00 in) Diameter
Wind Loading	Operational	80 km/h (50 mph)
	Survival	200 km/h (125 mph)
Temperature	-50°C to 80°C
Humidity	0 to 100% (Condensing)
Atmosphere	Standard Hardware Meets 500 Hour Salt Spray Test Requirements (ASTM B-117)
Solar Radiation	360 BTU/h/ft ²
Shock and Vibration	As Encountered During Shipping and Handling

(All specifications typical)



All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

VST-009.3

© 2012 Skyware Global