

3.8M Rx/Tx Dual Axis C or Ku-Band VSAT Antenna

Series 1386

Technical Specifications

Electrical		C-Band Linear	C-Band Circular	Ku-Band Linear
Antenna Size		3.8M (150 in.)	3.8M (150 in.)	3.8M (150 in.)
Operating Frequency (GHz)	Receive	3.625 - 4.20 GHz	3.625 - 4.20 GHz	10.95 - 12.75 GHz
	Transmit	5.845 - 6.425 GHz	5.845 - 6.425 GHz	13.75 - 14.50 GHz
Antenna Gain at Midband (± .2dB)	Receive	42.00 dBi	41.80 dBi	51.20 dBi
	Transmit	46.50 dBi	46.30 dBi	53.00 dBi
VSWR	Receive	1.3:1 max	1.3:1 max	1.5:1 max
	Transmit	1.3:1 max	1.3:1 max	1.3:1 max
Pattern Beamwidth (in degrees at midband)	-3 dB	Rx: 1.40° Tx: 0.90°	Rx: 1.40° Tx: 0.90°	Rx: 0.50° Tx: 1.00°
	-15 dB	Rx: 3.20° Tx: 2.00°	Rx: 1.40° Tx: 0.90°	Rx: 0.40° Tx: 0.90°
Sidelobe Envelope, Co-Pol (dBi)				
100λ / D < θ ≤ 20°		29 - 25 Logθ dBi	29 - 25 Logθ dBi	29 - 25 Logθ dBi
20° < θ ≤ 26.3°		-3.5 dBi	-3.5 dBi	-3.5 dBi
26.3° < θ ≤ 48°		32 - 25 Logθ dBi	32 - 25 Logθ dBi	32 - 25 Logθ dBi
θ > 48°		-10 dBi (averaged)	-10 dBi (averaged)	-10 dBi (averaged)
Antenna Noise Temperature	5° Elevation	55 K	62 K	70 K
	10° Elevation	45 K	52 K	60 K
	20° Elevation	38 K	45 K	55 K
	40° Elevation	36 K	43 K	45 K
Power Handling		1 kW	1 kW	100 W
Cross Polarization Isolation	On Axis	> 30 dB	Rx > 15.00 dB Tx > 17.70 dB	Rx > 30.00 dB Tx > 35.00 dB
	Within 1.0 dB Beamwidth	> 27 dB	Rx > 15.00 dB Tx > 17.70 dB	Rx > 25.00 dB Tx > 26.00 dB
Note: Standard C-Band Circular polarization in Tx-Band provides an axial ratio of 1.3 (XPD equivalence of 17.7 dB). Optional F-1 station feed available with axial ratio of 1.09 (XPD equivalence >27.3 dB) in Tx -Band. Call factory when specifying this option. X-Band filters available upon request.				
Output Waveguide Interface Flange	Receive	CPR 229	CPR 229	WR 75
	Transmit	CPR 137 or Type N	CPR 137 or Type N	WR 75

Mechanical	
Reflector Material	Glass Fiber Reinforced SMC
Mount Type	Dual Axis Motorized, Elevation over Azimuth, Galvanized Steel Construction
Actuators	Recirculating Ballscrews
Antenna Optics	Easy-to-assemble, 4 Pc., Offset Fed Prime Focus Design with 0.6 F/D optics
Mast Pipe Size	10" SCH 40 Pipe (10.75" OD) 27.3 cm
Elevation Adjustment Range	12° to 90° or 0° to 15° for Polar Latitudes
Azimuth Adjustment Range	360° Continuous with +/- 35° Fine Adjustment
Angular Tracking Travel	Elevation +/- 10°; Azimuth +/- 10° (within adjustment range)
Interface	Electrically to ACU
Tracking Accuracy	0.05°
Shipping Specifications	Approximate Net Weight: Weight (nominal) 1125 lbs. (511 Kg) Approximate Packaged Weight: Weight (nominal) 1882 lbs. (855 Kg)

Environmental Performance		
Wind Loading	Operational Survival	50 mph (80 km/h) 125 mph (201 km/h)
Temperature (operational)		- 40°to 140°F (- 40°to 60°C)
Rain (operational)		½" / hr
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Relative Humidity		0 to 100% with Condensation
Solar Radiation		360 BTU/h/ft2

GENERAL DYNAMICS
SATCOM Technologies

1000-059 Rev. 04/12

<http://www.SatelliteDish.com> 954-941-8883