



ALB130 Lite Series

Lite 8W/12W/16W
Ku-Band Block-Up Converter

This small and lightweight BUC is ideal for SOTM applications and also benefits fixed and maritime applications.

Designed to be mounted on the feed horn, the BUC has "Best in Class" efficiency and "lowest power consumption". The unit works on a wide range DC power supply of 38V to 60V. Innovative and efficient thermal design makes this BUC one of the smallest, robust, reliable and rugged enough to withstand outdoor conditions in the industry.

The unit can be configured to work in 1:1 redundant mode by adding on a simple redundancy option to the basic unit.

Quality Assurance

100% of all BUCs go through stringent quality checks in addition to well defined Electrical Stress Screening to ensure operation in harsh outdoor environments. The BUCs are also subjected to seal test for water ingress verification.

Reliability

Field proven under harsh environment conditions, Agilis ODUs can withstand temperature ranging from -40°C to +60°C with up to 100% humidity.

Features

- Compact and lightweight
- Can be powered directly from: iDirect X7 modem
- Best in class efficiency with less power consumption.
- Available in both standard and extended Ku-Band
- Forward power detection facility
- Intuitive monitoring & control through RS232/RS485 & Ethernet (SNMP & HTTP)
- Auto ranging 18 to 60VDC Power Supply
- Automatic fault identification & alarm generation
- Wide operating temperature range -40°C to +60°C
- IP65 rated housing (weather proof construction)
- RoHS compliant

ALB130 Lite Series

Lite 8W/12W/16W

Ku-Band Block-Up Converter

Technical Specifications

RF Specifications

Transmit Frequency	13.75 – 14.5GHz (EXT Ku) 14.0 – 14.5GHz (STD Ku)
IF Frequency Range	950 – 1700MHz (EXT Ku) 950 – 1450MHz (STD Ku)
L.O Frequency	13.05GHz (STD Ku) 12.8GHz (EXT Ku)
Output Power (P1dB)	39dBm (8W), 40.8dBm (12W) & 42dBm (16W)
Small Signal Gain	65dB Min (8W), 68dB Min (12W/16W)
Gain Flatness	±2dB over the O/P frequency band
Gain Variation	±2dB over the operating temperature range
Gain Control	20dB in steps of 0.5dB
Inter modulation	-25dBc @ Relative to combine power of two carriers at 3dB total power backoff from P1dB
O/P spurious	According to EN301428
Phase Noise @ Offset	
1KHz	-73dBc/Hz
10KHz	-83dBc/Hz
100KHz	-93dBc/Hz
I/P VSWR	1.5:1
O/P VSWR	1.25:1 (with optional external isolator)
Noise Power Density Tx BD	-70dBW/4KHz
Rx BD	-142dBW/4KHz

DC Power

Prime Power	24VDC (range 24 to 32VDC) 48VDC (range 38 to 60VDC) via external MS connector (IFL power optional) Can be powered via: iDirect X7 modem
Power Consumption	85W (Typical for 8W) 110W (Typical for 12W) 135 (Typical for 16W)

Interfaces

IF Input Interface	50Ohms N-type Female
Output Interface	WR 75G

External Reference

Frequency	10MHz
Power	-5dBm to +5dBm
External reference phase	
noise requirement @ frequency offset	
1 KHz	-135dBc/Hz
10 KHz	-145dBc/Hz
100 KHz	-155dBc/Hz

Monitor & Control

Monitor	BUC temperature Status alarm RF output power LED status indication
Control	Attenuation RF output mute
Interface	RS232/RS485 & Ethernet (SNMP & HTTP) via external MS connector
Tx Redundancy	External RCU (optional for 1+1 redundancy system requirement)

Environmental

Operating Temperature	-40°C to +60°C Optional (-40°C to +70°C for 16W)
Relative Humidity	Up to 100% Weather protection sealed to IP65

Mechanical

Size	160L x 93W x 85H mm
Weight	1.2kg
Color	White Powder Coat

Compliance Standard

IEC 609501-2nd Edition	International Safety Standard for Information Technology Equipment
ETSI EN 301 489-12	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) Standard for radio equipment and services; Part 12: Specific conditions for Very Small Aperture Terminal, Satellite Interactive Earth Stations operated in the frequency ranges between 4GHz and 30GHz in the Fixed Satellite Service (FSS)
ETSI EN 301 489-1	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility Standard for Radio Equipment and Services
FCC Class A	Two levels of radiation and conducted emissions Limits for unintentional radiators (FCC Mark)

Note: All specifications are subject to change without notice.
Rev. 240214

