## **Product Specifications**



### LS2-HMHM-D

D-CLASS LSF2-50 SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male, variable length

• WARNING: DO NOT MATE WITH 4.1-9.5 DIN



### **Product Classification**

Product Series LSF2-50

Product Type Wireless transmission cable assembly

### **General Specifications**

Body Style, Connector A Straight
Body Style, Connector B Straight
Interface, Connector A 4.3-10 Male
Interface, Connector B 4.3-10 Male
Nominal Size 3/8 in
Specification Sheet Revision Level A

Variable Length For custom lengths contact 828-324-2200 or 1-800-982-1708 (toll free), or your local

CommScope representative

### **Electrical Specifications**

3rd Order IMD Dynamic -162.00 dBc | -119.00 dBm 3rd Order IMD Dynamic Test Method Two +43 dBm carriers per IEC 62037

### **Jumper Assembly Sample Label**

# Product Specifications

LS2-HMHM-D



### **Return Loss/VSWR**

Frequency Band	VSWR	Return Loss (dB)
698-960 MHz	1.07	30.00
1700-2200 MHz	1.07	30.00
2200-2700 MHz	1.08	28.00
3400-3800 MHz	1.11	26.00
4000-6000 MHz	1.17	22.00

### **Regulatory Compliance/Certifications**

### **Agency**

RoHS 2011/65/EU China RoHS SJ/T 11364-2006

ISO 9001:2008

#### Classification

Compliant by Exemption

Above Maximum Concentration Value (MCV)

Designed, manufactured and/or distributed under this quality management system



