

China Starwin 11.3M EARTH STATION ANTENNA DATASHEET



Super 11.3m antenna

Performance Strength

- *C,Ku, multi band, extended band Available , meeting FCC and ITU-RS-580 requirements
- *High quality aluminum reflector panels and galvanized steel backup structure
- *Self-aligning aluminum antenna reflector-no field alignment
- *Galvanized steel elevation over azimuth pedestal
- *Fixed foundation and Non penetrating foundation optional for wider choice
- *Survives 125 mph winds in any position and High wind configuration optional

Description

China Starwin 11.3m antenna delivers exceptional high performance for transmit/receive application in C, Ku, ka, X band in Tx/Rx 2 ports ,4 ports or Rx 2 ports with high gain ,low noise and low microwave interference.

China Starwin 11.3m antenna offers a fine reflector design with a stretch formed double contoured panels, strong back struts and hub fore ease of field alignment. The standard designed azimuth over elevation pedestal provides a cost-effective solution for ground or roof installation with high stiffness and stability , full orbital arc coverage and fine drive performance, and ensures the pointing and tracking accuracy.

The electrical performance is compliant with FCC and ITU-RS-580 sidelobe specifications and Intelsat, Eutelsat, INMARSAT, ASIASAT,APT and CHINASAT, etc requirement.

China Starwin Science&Technology Co., Ltd.

Tel:+8629-87650669,E-mail:sales@starwincom.com,<http://www.starwincom.com>

Copyright©2013 Starwin

Key features

- *Meets or exceeds CCIR 580 and INTELSAT Requirements
- *High G/T, excellent pattern characteristic
- * Precision compression molded offset antenna
- *CP/LP switchable feed
- * Hot dip zinc steel pedestal, hub & back struts
- *Galvanized stainless steel fasteners
- * Foundation hardware kit provided
- * Package suitable for air, ocean land transportation

Antenna Accessory

- *Limit Switches
- *Foundation hardware Kit
- *Grounding Kits Cable –Mounting kits
- *Cable mounting kits
- *ODU Support Kits
- *Factory Feed System Testing and Documentation
- *Ocean /Air/land Transport Packing

Options

- * L, S, C, X, Ku and DBS-band feed configurations
- *800MHz bandwidth is available
- *Two or four ports -Tx/Rx port in linear or circular polarized feeds
- *motorization kits
- *Feed blower or deicing with automatic controls
- *Lightning Rod Kits
- *Non-penetrating mount
- * Kingpost pedestal, Rotation platform optional
- * Antenna control & tracking system for step track, program track, inclined orbit track
- * Integrated LNB or LNA systems
- *HPAs, converters and M&C systems
- * Turnkey installation & testing

Continue to next page

Electrical, Mechanical, Environmental Specification

Electrical Specification For 11.3m Super antenna

Type	SWSP110C		SWSP110K	
Operating Frequency, GHz	C-Band		Ku-Band	
	Receive	Transmit	Receive	Transmit
	3.4~4.2	5.85~6.425	10.95~12.75	13.75~14.5
Gain, Mid-band, dBi	50.84	55.0	61.4	62.32
Polarization	Linear/Circular		Linear	
XPD(on Axis), dB	35	35	35	35
XPD across 1dB Beam Width, dB	33	33	33	33
Axial Ratio (Circular-Polarized)	2-Port Feed	1.30	1.09	
	4-Port Feed	1.06	1.06	
VSWR	1.25	1.25	1.25	1.25
Antenna Noise Temperature	2/4 Port Feed		2/4 Port Feed	
10° Elevation	39K/ 49 K		64K/ 89 K	
30° Elevation	30K/ 37 K		54K/ 75 K	
50° Elevation	27K/ 33 K		48K/ 63 K	
-3 dB Beam Width, Mid-band	0.43°	0.285°	0.14°	0.126°
Typical G/T (EL>10° , 2-port)	33.8dB/K (30° LNA)		39dB/K (70° LNA)	
Tx. Power Capability, KW		5		2
Feed Interface	CPR—229F	CPR—159G/137G	WR-75	WR-75
Feed Insertion Loss, dB	0.2/0.25	0.2/0.25	0.25/0.35	0.25/0.4
Isolation, Tx to Rx, dB		85		85
Tx/Tx ,Rx /Rx, Linear , dB		30		30
Tx/Tx ,Rx /Rx, Circular , dB		20		20
Side lobe	CCIR 580			

Mechanical Specification

Antenna Diameter	11.3m
Antenna Type	Cass grain
Surface Accuracy(RMS)	≤0.4mm
Antenna pedestal type	Kingpost type, rotation platform optional
Antenna Pointing Range	Azimuth ±85°/0°~360° Elevation 0°~90°(Continuous) Polarization ±90°(Continuous)
Drive Mode	Manual or Motorized
Motor Drive System	Azimuth or Elevation Travel Rate 0.02°/S-0.04°/S Polarization Travel Rate 1°/S
Antenna reflector Material	Aluminum Alloy

China Starwin Science&Technology Co., Ltd.

Tel:+8629-87650669,E-mail:sales@starwincom.com,<http://www.starwincom.com>

Copyright©2013 Starwin

Finish of steel parts	Hot spray Zinc
-----------------------	----------------

Environmental Specification

Operational Wind	79km/h gusting to 126km/h
Survival Wind	198km/h
Temperature	-40°~+60°
Relative Humidity	100%
Solar Radiation	1135Kcal/h/m ²
Seismic(Survival)	0.3g(H), 0.15g(V)
Ice Loading	13mm Operational; 30mm Survival