



| |
|-----------------|
| Redundant HDMI |
| HD-SDI 1080p |
| CVBS Baseband |
| Dual CVBS AV |
| YPbPr + S-Video |
| YPbPr + HDMI |

Thor DVB-S/S2 Encoder & Modulator is an integrated HD Video Encoder with the satellite S2 modulator. Hot-swappable modules with different video inputs (CVBS/SDI/HDMI/YPbPr...) are available.

It has also 1 channel ASI input for external TS (MPEG2 or H.264) multiplexing. It outputs ASI and DVB-S/S2 RF (IF Optional) simultaneously.

The signal source could be SDI camera, HDMI Blue-ray players and etc. It has web-based NMS GUI interface for easy online management.

Featuring its high performance and low cost, the S2 is especially used by TV stations or SNG systems to encode SD/HD programs and output to uplink.

Base Main Model H-1SDI-DVBS2 has 1 HD/SD-SDI input and L-Band RF DVB-S/S2 Output

Additional Model Selection :

Configuration page for S2 modulator with Lband 950-2100 Mhz RF output; or IF: 50-2

**1 HD/SD-SDI Input / L-B
RF DVB-S/S2 Output**

H-1SDI-DVBS2

H-1SDI-DVBS

H-1SDI-DVBS-IF

1 HD/SD-SDI Input / IF Output

H-1HDMI-DVBS

H-1HDMI-DVBS-IF

**1 HDMI video Input / L-Band RF DVB-S/S2 Output
1 HDMI Input / IF Output**

H-1CVBS-DVBS

H-1CVBS-DVBS-IF

**1 CVBS Video Input / L-Band RF DVB-S/S2 Output
1 Analog CVBS Input / IF Output**

H-1RGB-DVBS

H-1RGB-DVBS-IF

**1 YPbPr Video Input / L-Band RF DVB-S/S2 Output
1 YPbPr Video Input / IF Output**

Product Specifications

low 70-250mn latency models available



SatelliteDish.com®

(954) 941-8883