

- Simple IF (See Model #RY-RRS11) or L-Band (Model #RY-RRS11L) Switching for DM240XR Modulators
  - Easy Access to Connectors and LEDs
  - Front Panel Monitor Ports
  - Configuration: Modulator Only
  - Switch Time: 1 msec Maximum from
  - Control Port Input
  - Rear Panel Ports: L-Band: SMA, 50 Ohms
  - IF: BNC, 75 Ohms (Optional, see Model # RY-RRS11)
  - Return Loss: L-Band: 14 dB
  - IF: 20 dB (See Model #RY-RRS11)
  - Front Panel Monitor Ports: L-Band: BNC, 50 Ohms
  - IF: BNC, 75 Ohms (Optional, see Model #RRS11)
  - Primary Control Port: DB-9 Male
  - Backup Control Port: DB-9 Male
  - Status Port: DB-9 Male
- 
- - Prime Power: No internal power supplies.
  - Redundant power supplied from
  - DM240XR via DB-9 Control Port
  - Operating Temperature: 0 to 50°C, 95% Humidity, Non-Condensing
  - Storage Temperature: -20 to 70°C, 99% Humidity, Non-Condensing
- 
- - Size: 19" W x 17" D x 1.75" H
  - 48.3 x 43.2 x 4.45 (cm)
  - Weight: 8.0 Pounds (03.62 Kg)



**SatelliteDish.com** ®

(954) 941-8883