

...communicating at the speed of light

## FT-FOTRHQ-1VD-ST-S

# Baseband Video Transmitter and Receiver With Bi-Directional Multi-Protocol Data Transmission

# Features:

- 10 Bit digital video transmission
- High speed synchronization with digital transmission technology
- · Wide optic dynamic range, no adjustments required
- · LCD Indicators for power, optic, video & data
- Immunity to electrical interference, ground loops & radio frequency interference
- Safe, clear transmission in bad electromagnetic environments
- Surface mount technology design
- · Video DC restoration
- Supports RS485, RS422 or RS232



### **Description:**

The FT-FOTRHQ-1VD-ST-S fiber optic transmitter/receiver supports the transmission of a single baseband video channel and single channel of bi-directional, multi-protocol data over one strand of single-mode fiber optic cable. This product is compatible with all NTSC and PAL video signals. Power, optical signal, video signal and data signal are easily inspected through LED indicators directly on the units. The transmitter and receiver combination supports transmission distances for optical loss budgets of less than 16 dB.

## Specifications:

0	pti	cal		
_			_	

Optical Wavelength: 1310nm / 1550nm Fiber Type: Single-mode 9/125µm

Max. Link Distance: 12.5 miles
Connector: Simplex ST
Acceptable loss budget: 16 dB

#### Video

Tilt:

Number of Inputs: 1

 $\begin{array}{ll} \mbox{Video Connector:} & \mbox{BNC Female} \\ \mbox{Input Impedance, Transmitter:} & \mbox{75}\Omega \mbox{ (Unbalanced)} \\ \mbox{Output Impedance, Receiver:} & \mbox{75}\Omega \mbox{ (Unbalanced)} \\ \end{array}$ 

<1%

Video Input Level: 1V p-p
Video Input Overload Level: >1.5V p-p
Video Bandwidth per Channel: 5Hz - 10MHz
Video SNR: >67 dB
Differential Gain: <1%
Differential Phase: <1°

## **Ordering Information:**

FT-FOTRHQ-1VD-ST-S

#### Data

Data Rate: DC - 250Kbps
Data Interface: RS485, RS422 or

RS232

Baud Rate Per Channel: 0 - 100Kbps

Bit Error Rate: <10<sup>-9</sup>

Connector: Terminal Block

#### General

Power Supply: 12VDC Power Consumption: 2.8W

Operating Temperature: -40°F - 167°F Storage Temperature: -40°F - 185°F

Operating Humidity: 0-95%

(Non-condensing)

## **Contents Include:**

- 1 Transmitter
- 1 Receiver
- 2 Power supplies
- 1 Instruction manual

Email: sales@fibertronixparts.com Web: www.fibertronixparts.com