



ELECTRICAL SPECIFICATION

Operational	C-Receive	Ku- Receive
Frequency(GHz)	3.4-4.2	10.95-12.75
Antenna Gain(dB)	47.59	56.93
VSWR	1.25:1	1.3:1
Beam Width : -3dB	0.68°	0.23°
Polarization	Linear Polarized	Linear Polarized
Axis Ratio for circularPol.	0.5dB	
Noise Temperature (°K)	2 port feed	
10°EL	35	65
20°EL	30	55
40°EL	26	50
Feed Interface	CPR-229G	WR-75

Feed Insertion Loss(dB)	0.3	0.5
Port Isolation	Isolation between ports for LinearPol.≥30dB Isolation between ports for circularPol.≥20dB	
XPD	On Axis ≥35dB	
	Across 1dB beam width ≥33dB	
Side lobes	CCIR580	
MECHANICAL SPECIFICATION		
Antenna Type	Ring-focus Antenna	
Antenna Mount Type	Kingpost pedestal	
Surface Accuracy (R.M.S)	≤0.35mm	
Azimuth Travel Range	± 85°	
Elevation Travel Range	0°~ 90°	
Antenna Drive Mode	Motorized	
ENVIRONMENTAL SPECIFICATION		
Operational Wind	45mi/h (72km/h) to 60mi/h (97Km/h)	
Survival Wind	125mi/h (200Km/h)	
Temperature	-45°~ +60°	
Relative Humidity	0% ~ 100%	
Seismic	Horizontal	0.3g
	Vertical	0.15g
Snow	30mm	
Ice	25mm	

