

DATUM SYSTEMS

PRECISION SATELLITE MODEMS

PRODUCT PRESENTATION SHEET

MODEM PSM-500LT L-BAND SATELLITE TERMINAL



Key Highlights

- FlexLDPC Multi Block Sizes & Code Rates
- Internal BUC and LNB Power
- High Stability 10 MHz Reference
- 1.2 kbps to 29.5 Mbps
- BPSK/QPSK/OQPSK/8PSK/8QAM/16QAM
- TPC, Viterbi, TCM, Reed Solomon
- Most FEC Types and Modcods
- Std and Adv Ethernet IP Interfaces
- Bridge and Router Modes, QoS
- SCPS - TCP/IP Acceleration
- Dual G.703/E1, Full/Fractional D&I (N X 64)
- Lowest Latency, <15 ms at 64 kbps $\frac{3}{4}$ QPSK
- Typical acquisition time, 71 ms at 64 kbps
- Async Channel, AUPC
- Remote Modem Control Channel
- Tx Output of 40 dB, +5 to -35 dBm
- Optional SNMP Remote Interface
- Web Browser GUI

Applications

- Cellular Backhaul
- Enterprise
- IP Networks
- On-the-Move
- Bandwidth on Demand

Architectures

- Point-to-point
- Point-to-Multipoint
- Mesh
- Multicasting
- Unidirectional

Datum System's PSM-500LT L-Band Satellite Terminal combines the performance and reliability of our M500 Series modems with an integrated BUC Power Supply and High Stability 10 MHz reference. The PSM-500LT is the industry's most versatile, reliable and efficient remote satellite modem. It is unmatched by any other modem for its BER performance, fast acquisition, low latency and total power/bandwidth optimization.

Advanced FlexLDPC – With unparalleled configuration flexibility and superior coding gain, FlexLDPC takes FEC technology innovation to the next level, bringing strong economic advantages to satellite service providers and their customers. Granular code rates and block sizes get you the most out of your available satellite bandwidth and spectral power, while keeping processing latency at the desired level.

Internal BUC/LNB Power & Reference – The PSM-500LT provides BUC and LNB power from an integrated power supply. A High Stability 10 MHz reference is also provided through the modem Transmit (N-Type) and Receive (F-Type) connections at the rear. Reference, BUC and LNB power may be disabled via the front panel. Front panel voltage and current measurements are available for BUC and LNB monitoring.

SCPS - TCP/IP Acceleration – Datum Systems provides an embedded protocol acceleration option based on the Space Communication Transport Specification (SCPS-TP). Our integrated optimization software provides increases in IP packet throughput over TCP/IP links via our Ethernet IP interface option.

Feature Unlocks – The PSM-500LT can be easily upgraded via front panel key codes. Upgrades are simple to implement and are available in preconfigured software versions, offering a variety of options for modulation, FEC and data rates up to 29.5Mbps.

Redundancy Built-in 1:1 redundancy comes standard on the PSM-500LT and supports BUC/LNB power and reference switching. It can be enabled through the front panel and requires only a few external cables and power splitters.



DATUM SYSTEMS, INC
15 GREAT OAKS BLVD
SAN JOSE, CA 95119

WWW.DATUMSYSTEMS.COM
TEL: (408) 365-9745
FAX: (408) 365-0471



System Specifications:

Operating Modes: Rx and Tx Continuous (SCPC), Optional Tx Burst
 Tx Tuning Range: 950 to 1750 MHz, in 1 Hz Steps
 Rx Tuning Range: 950 to 1900 MHz, in 1 Hz Steps
 Data Rate Selection: 1 bps increments
 Data Rate Minimum: 1.2 kbps rate 1/2 BPSK
 Data Rate Maximum: 29.52 Mbps rate 3/4 8PSK
 Data Rate Accuracy: Accurate to 2 x 10⁻¹² of relative clock reference
 Symbol Rate Range: 2.4 ksp/s to 14.76 Msp/s in 1 bps step sizes
 Available Modulation: BPSK, QPSK, OQPSK, 8PSK, 8QAM, 16QAM
 Available TPC Modes: M5 Full, Short & Legacy, Comtech and Advanced
 Concatenated RS: Selectable N & K, IESS 308/309/310 and CT Comp
 Reed Solomon Depth: 4, 8 or 16
 FEC Options:
 Viterbi - 1/2, 3/4, 5/6, 7/8 (k = 7) Trellis - 2/3
 TPC-4K 1/2, 3/4, 7/8, 0.95, 21/44
 TPC-16K 1/2, 3/4, 7/8, 0.922, 0.453
 FlexLDPC 1/2, 2/3, 3/4, 14/17, 7/8, 10/11, 16/17

FlexLDPC™	Typical Eb/No for 1E-8 BER				Delay @ 64kbps
	QPSK	8PSK	8QAM	16QAM	
LDPC-1/2 - 2k	2.04 dB	n/a	3.80 dB	4.48 dB	49.6 ms
LDPC-1/2-4k	1.73 dB	n/a	3.44 dB	4.16 dB	98.0 ms
LDPC-1/2-8k	1.52 dB	n/a	3.19 dB	3.92 dB	195.0 ms
LDPC-1/2-16k	1.38 dB	n/a	3.04 dB	3.76 dB	388.6 ms
LDPC-2/3-2k	2.77 dB	4.88 dB	4.68 dB	5.85 dB	44.4 ms
LDPC-2/3-4k	2.46 dB	4.53 dB	4.36 dB	5.46 dB	87.5 ms
LDPC-2/3-8k	2.23 dB	4.28 dB	4.09 dB	5.19 dB	173.7 ms
LDPC-2/3-16k	2.09 dB	4.14 dB	3.91 dB	5.01 dB	346.1 ms
LDPC-3/4-2k	3.52 dB	5.97 dB	5.51 dB	6.78 dB	41.9 ms
LDPC-3/4-4k	3.14 dB	5.56 dB	5.11 dB	6.37 dB	82.4 ms
LDPC-3/4-8k	2.89 dB	5.27 dB	4.83 dB	6.07 dB	163.1 ms
LDPC-3/4-16k	2.72 dB	5.07 dB	4.63 dB	5.87 dB	325.0 ms
LDPC-7/8-2k	4.96 dB	7.89 dB	6.98 dB	8.48 dB	38.1 ms
LDPC-7/8-4k	4.32 dB	7.21 dB	6.40 dB	7.84 dB	74.6 ms
LDPC-7/8-8k	4.00 dB	6.86 dB	6.05 dB	7.51 dB	147.3 ms
LDPC-7/8-16k	3.90 dB	6.66 dB	5.87 dB	7.32 dB	293.6 ms
LDPC-10/11-2k	5.63 dB	8.73 dB	7.68 dB	9.37 dB	37.0 ms
LDPC-10/11-4k	5.00 dB	7.99 dB	7.02 dB	8.63 dB	72.3 ms
LDPC-10/11-8k	4.58 dB	7.51 dB	6.60 dB	8.18 dB	143.0 ms
LDPC-10/11-16k	4.40 dB	7.33 dB	6.35 dB	7.95 dB	284.5 ms

Guaranteed Eb/No is 0.2 dB > Typical

Modulator:

Transmit Output Power: +5 to -35 dBm in 0.1 dB steps (max +3 dBm @ 50Ω)
 IF Tx Impedance: 50Ω (Type N)
 Return Loss: 14 dB typical, 10 dB minimum
 Output Phase Noise: Better than IESS-308/309 by 6 dB typical, 4 dB min
 Level Stability: ±0.5 dB, 0 ~ 50°C, MHz at 25°C
 Level Accuracy: Accurate ±0.5 dB, 950 ~ 1750
 Output Spurious: < -55 dBc/4 kHz, Typical < -65 dBc/4 kHz
 Carrier on/ off Isolation: > 60 dB

Scrambler Types:

IBS, V.35, IESS, TPC, RS, LDPC, EFD
 Data Clock Sources: Internal, Terminal Timing, External, Rx Recovered
 Internal Stability: 1 x 10⁻⁸ OCXO (Standard)
 External Reference: 1, 2, 5 or 10 MHz input on rear panel

Transmit BUC Power:

Nominal 24 VDC, 100 Watts (Or 12/36/48 VDC)
 Max 60 VDC/6A up to 250 Watt
 Transmit BUC Reference: 10 MHz at nominal -3 dBm internal or external
 Reference Stability: 1 x 10⁻⁸ OCXO, 2 x 10⁻⁷/year aging (L-Band)
 Reference Phase Noise: -110 dBc @ 10 Hz, -130 dBc @ 100 Hz, -140 dBc @ 1 kHz,
 -150 dBc @ 10 kHz, -155 dBc @ 100 kHz

Demodulator:

Rx Carrier Input Range: -20 to -70 dBm, scales to -101 dBm at lower rates (minimum = 10 log(symbol rate) - 135 dBm)
 IF Tx Impedance: 75Ω Type F -Connector
 Return Loss: 10 dB minimum
 Max Composite Input: -5 dBm or +40 dBc, whichever is lower power
 Input Phase Noise: Better than Intelsat by 6 dB typical, 4 dB min
 Rx Acquisition Range: Programmable from ± 100 Hz to ± 1.25 MHz
 Descrambler Types: IBS, V.35, IESS, TPC, RS, LDPC, EFD

Fast Receive Lock Performance:

Example: FEC 1/2, EB/NO = 6.0 dB, Acquisition Range of ± 30 kHz
 • 315 ms at 9.6 kbps QPSK
 • 175 ms at 9.6 kbps BPSK
 • 71 ms at 64 kbps QPSK

Plesiochronous or Doppler Buffer Store:

Standard Buffer Range: 4 bits to 524,280 bits, in 1 bit steps or delay time
 Receive Clock Options: Internal, External, Mod Clock, Receive Clock

Terrestrial Interfaces:

Standard Synchronous: Serial RS232, RS422, V.35, V.36, EIA-530(A)
 Optional:
 HSSI
 Ethernet IP 10/100 Base-T (Bridge & Router, QoS)
 TCP/IP Acceleration (Software Only)
 -Supports Up to 5 Mbps Aggregate throughput and 200 Continuous Sessions
 Advanced Ethernet IP, GigE, High PPS Throughput, Vyatta Bridge/Router Dual G.703/E1 (D&I), Dual Bal Inputs (RJ-45), UnBal (BNC) Opt Full E1, PCM-30 (CAS), PCM-31 (CCS), N X 64, N = 1 to 31 Time Slots

Multiplexer and Overhead Features:

IBS Multiplexer: Built-in IBS Overhead Channel with standard and enhanced variable rate RS232 and RS485.
 Supports Automatic Uplink Power Control (AUPC), Remote Modem Control Interface and 2 Form-C Backward Alarms

Monitor and Control:

Front Panel: LCD and Keyboard for easy control and status
 Terminal Mode: Full screen interactive display of all parameters
 Remote Packet Mode: Packet driven RS232/RS485 control and status
 Optional Web Browser: Available through the Ethernet Interface SnIP
 SNMP Available through the Ethernet Interface SnIP

Diagnostics:

Loopback Modes: IF, bi-directional terr and sat data loopbacks
 BER Test Pattern: 2047 or 2 23-1
 BERT: Built-in bi-directional bit error rate test set
 Carrier: Pure carrier and sideband
 Form C Relays: Assignable faults to Form C rear alarm connector

Environmental and Physical

Prime Power Input: 90 to 264 VAC, 50/60 Hz, -48 VDC (HW Option), < 30 watts, 220 Watts Max fully loaded including internal BUC and LNB power
 BUC Power Options: 24 VDC @ 160 Watts, 5A max w/PFC
 48 VDC @ 160 Watts, 3.2A max w/PFC
 LNB Output Power: Selectable: Off, 13 or 18 VDC
 Power Factor Correction: Optional at all power levels
 Operating Conditions: 0 to 50°C, to 95% humidity, non-condensing
 Storage Temperature: -20 to +70°C, 99% humidity, non condensing
 Size: Rack mount - 1 RU (19"W x 12"D x 1.75"H)
 Weight: Approximately 7 lbs fully configured

Certifications and Compliance:

CE Certified for: EN50022 Class B (Emissions)
 EN50082-1 Part 1 (Immunity)
 Can/CSA C222 No. 950-95 (Safety)
 UL-1950 (Safety)



RoHS Compliant: Meets RoHS lead-free standards

