

## Product Application



## Product Specifications

<i>* All Specifications Subject to Change Without Notice</i>	
Input	HDMI up to 1080p60
Supported Resolutions	1280x720P 60 / 59.94 / 50 Hz 1920x1080i 60 / 59.94 / 50 Hz
Video Codecs	MPEG-2 HD 1.5-19.5 Mbps H.264 HD 0.8-19.5 Mbps
	MPEG-1 Layer II, MPEG-2 AAC,

Audio Codecs	MPEG-4 AAC, AC-3 Dolby Audio Dolby Passthrough
Audio Sample Rate	48 kHz
Audio Bit Rates	64 kbps, 96 kbps, 128 kbps, 192 kbps, 256 kbps, 320 kbps
RF Frequency Range	30-960 MHz 1 kHz Step
RF Power Level	Adjustable 5-35 dBmV
DVB-ASI Output	BNC Connector: 1-60 Mbps
DVB-ASI Input	BNC Connector: 1-120 Mbps Programs Selected by the PID Programs Muxed to all Outputs
IPTV Output	MPTS MPEG-TS over UDP Unicast and Multicast Supported
Power Input	100-240 VAC Auto Switching ~ 20
Dimensions	19 x 17 x 2 Inches
Weight	9 Pounds
Operating Temperature	32-110 F

