

SPI-14/18-2150

400-2150MHz Satellite Inline Power Inserter



Features

- TruSpec power inserters supply constant DC voltage to C/Ku or DSS Satellite LNBs, microwave down converters and in-line amplifiers
- Plug-in external UL power wall adapter included
- Input voltage 120 VAC 60 Hz 35 W
- Operating frequency 400 MHz to 2150 MHz
- 2 Independent paths
- Output voltage selection switch 13 to 14/17 to 18 or 17 to 18/17 to 18 VDC 1000 mA
- Insertion loss 2 dB \pm 1 dB
- Isolation 65 dB
- UL-approved external universal AC power adapter for domestic and international use.



Power Adapter

Specification

| | |
|-----------------------|------------------------|
| Bandwidth | 400 MHz to 2150 MHz |
| Insertion Loss | 2 dB |
| Isolation | 65 dB |
| Input Connector | 75 Ω , F-Female |
| Output Connector | 75 Ω , F-Male |
| Input Voltage | 117 VAC |
| Output Voltage Port 1 | 18 VDC |
| Output Voltage Port 2 | 14/18 VDC sw. |
| LNB Current Each Path | 1000 mA |

Ordering Information

SPI-14/18-2150 400 MHz to 2150 MHz Satellite Inline Power Inserter