



The VTS-5754G pulsed-coupled cavity TWT covers 2.7 GHz to 3.1 GHz with 160 kW peak output power, up to 6% duty cycle. This device has a non-intercepting grid pulsed and single stage depressed collector to achieve 48 dB gain. This device is capable of parallel operation from a common HV power supply, phase tracking is better than +/- 20 degrees. The long life CD coated cathode is capable of pulse width to 200 micro seconds.

Typical Operating Parameters

PARAMETER	MIN	MAX	UNITS
Cathode Voltage	-46	-43	kV
Cathode Current	14	17	a
Heater Voltage	8	11	V
Heater Current	6	11	A
Collector Voltage	27	30	kV
Grid Bias Voltage	-700	-600	V
Grid Pulse Voltage	600	800	v
RF Drive Power	---	2.0	W
Pulse Width	---	100	isec
Duty Cycle	---	2.0	%
Collector Flow Rate	---	6.0	Gpm
Cooling Flow Rate	---	3.5	Gpm
Collector Pressure Drop	---	25	psig
Body Pressure Drop	---	42	psig
Weight	---	150	lbs
Dimensions	---	12 X15X 54	inches

Features

- 2.7 GHz to 3.1 GHz
- 160 kW PEAK OUTPUT POWER
- Up to 6% DUTY CYCLE
- NON-INTERCEPTING GRID PULSED
- 47 dB GAIN
- SINGLE STAGE DEPRESSED COLLECTOR
- FORCED LIQUID COOLED
- PPM FOCUSED
- COAXIAL TYPE-N- INPUT, CPR 284 WAVEGUIDE OUTPUT



SatelliteDish.com ®

(954) 941-8883