

...communicating at the speed of light

Features:

- 8 Bit digital video transmission
- High speed synchronization with digital transmission technology
- · Wide optic dynamic range, no adjustments required
- · LCD Indicators for power, optic, video & data
- Immunity to electrical interference, ground loops & radio frequency interference
- Safe, clear transmission in bad electromagnetic environments
- Surface mount technology design
- · Video DC restoration
- Supports RS485, RS422 or RS232

And Receiver With Reverse Data Transmission For PTZ Cameras

FT-FOTR-2VD-ST-S
Dual Baseband Video Transmitter



Description:

The FT-FOTR-2VD-ST-S fiber optic transmitter/receiver supports the transmission of two baseband video channels and a single reverse data signal over one strand of single-mode fiber optic cable. This product is compatible with all NTSC and PAL video signals. Power, optical signal, video signal and data signal are easily inspected through LED indicators directly on the units. The transmitter and receiver combination supports transmission distances for optical loss budgets of less than 18 dB.

Specifications:

рt	

Optical Wavelength: 1310 nm / 1550 nmFiber Type: Single-mode 9/125 μm

Max. Link Distance: 12.5 miles
Connector: Simplex ST
Acceptable loss budget: 18 dB

Video

Number of Inputs: 2

 $\begin{array}{ll} \mbox{Video Connector:} & \mbox{BNC Female} \\ \mbox{Input Impedance, Transmitter:} & 75\Omega \mbox{ (Unbalanced)} \\ \mbox{Output Impedance, Receiver:} & 75\Omega \mbox{ (Unbalanced)} \\ \end{array}$

Video Bandwidth per Channel: 0 - 6.5MHz
Video SNR: >60 dB
Differential Gain: <1%
Differential Phase: <1°
Tilt: <1%

Ordering Information:

FT-FOTR-2VD-ST-S

Data

Data Rate: 0 - 300Kbps
Data Interface: RS485, RS422 or

RS232

Baud Rate Per Channel: 0 - 100Kbps

Bit Error Rate: <10⁻⁹

Connector: Terminal Block

General

Power Supply: 5VDC Power Consumption: <10W

Operating Temperature: 14°F - 122°F Storage Temperature: -22°F - 158°F

Operating Humidity: 0-95%

(Non-condensing)

Contents Include:

- 1 Transmitter
- 1 Receiver
- 2 Power supplies
- 1 Instruction manual

Email: sales@fibertronixparts.com Web: www.fibertronixparts.com