

9350 Satellite Router



Network Configuration *

Compatibility	Evolution® and iDirect Velocity™ compatible		
Network Topology	DVB-S2 with Adaptive TDMA Returns		
	Downstream	Upstream	
	DVB-S2/ACM	Adaptive TDMA	
Modulation	QPSK, 8PSK, 16APSK, 32APSK	BPSK, QPSK, 8PSK, 16QAM	
FEC	LDPC 1/4-8/9	2D 16-State 1/2-6/7	
Maximum Rates	Symbol	45 Msps	29 Msps
	<i>Maximum downstream and upstream data rates cannot be achieved simultaneously Maximum rates are achieved with optimal configurations</i>		
Spread Spectrum	Spreading Factor	2, 4 and 8	
	Max Chip Rate	29 Mcps	

Interfaces

SatCom Interfaces	Tx: Type-N, 950-2400 MHz, Composite Power +5dBm/-35dBm, 50Ω Rx1: TNC, 950-2150 MHz, -5dBm (max) composite / -130+10*log10 (Sym rate) dBm (min) single carrier, 50Ω Rx2: TNC, 950 - 2150 MHz, -5dBm (max) composite / -130+10*log10 (Sym rate) dBm (min) single carrier, 50Ω RX Monitor: TNC, 50Ω Software controllable 10/50 MHz reference on Tx, Rx1 and Rx2
Available BUC Power (IFL)	+24V, 5A max available @ connector +48V, 5A max available @ connector
Available LNB Power (IFL)	Rx1/Rx2: 13-19V @ 0.45A, 22KHz DiSeqC tone
Data Interfaces	LAN: 8-port switch, 10/100/1000, 802.1q VLAN, Additional 10/100/1000 port on front
I/O	RS-232: RJ45 (Console connection), Additional console port on front, RS-232 NMEA GPS, RS-232 GPS input for antenna Control Signaling, RS-422 Keyline, RS-422 BUC control, RS-422 Filter select
Protocols Supported	TCP, UDP, ACL, ICMP, IGMP, RIPv2, Static Routes, NAT, DHCP, DHCP Helper, Local DNS Caching, OpenAMIP, cRTP and GRE
Security	AES FIPS 140-2 Level 3**, Link Encryption (256-bit), TRANSEC, X.509 digital certificates authentication, Automatic Key Management
Traffic Engineering	Group QoS, QoS (Priority Queuing and CBWFQ), Strict Priority Queuing, Application Based QoS, Minimum CIR, CIR (Static and Dynamic), Rate Limiting
Other Features	Built-in Automatic Uplink Power, Frequency and Timing Control, Authentication, Antenna Control Interface (OpenAMIP), Supports Multiprotocol Encapsulation (MPE), Low-Speed COTM, Zeroize button

Mechanical/Environmental

Size	W 17.13 in x D 13.09 in x H 1.75 in (W 43.51 cm x D 33.25 cm x H 4.45 cm)
Weight	11.25 lbs (5.10 kg)
Operating Temperature	-40° to +60°C (-40° to +140°F)
Altitude	Operational: Up to 15,000 ft (4,572m); Storage: Up to 50,000 ft (15,240m)
Humidity	95% non-condensing humidity
Input Voltage	100-240 VAC, 50-60Hz 36-76 VDC (with DC power supply)
Certifications	FCC, CE, TUV, and RoHS compliant WGS**, Meets MIL-STD 810G

**Certification pending

*Above specs are Evolution only and software dependant.
Specifications are subject to change without notice